

# Plugs/connecting cables for PLS/PLS SL

## PLS-C

	Length	Sales unit (piece)	Article number	Picture
Mains connection cable with safety plug and GST18/3 socket	1.0 m	1	17399091090	
		5	17399591090	
	3.0 m	1	17399095090	
		5	17399595090	
Mains connection cable with GST18/3 plug	1.0 m	1	17399091092	
		5	17399591092	
	3.0 m	1	17399095092	
		5	17399595092	
Mains connection cable with GST18/3 socket	1.0 m	1	17399091091	
		5	17399591091	
	3.0 m	1	17399095091	
		5	17399595091	
Connecting cable with GST18/3 plug and socket	0.5 m	1	17398089093	
		5	17398589093	
	1.0 m	1	17398091093	
		5	17398591093	
	2.0 m	1	17398093093	
		5	17398593093	

## Sockets

### PPS



NEMA 5-15

Data	PPS D	PPS F	PPS USA	Unit
Article number	17401000000	17402000000	17403000000	
Rated voltage	250 V AC		125 V AC	
Nominal current	10 A DC / 16 A AC		15 A AC	
Contact material	CuZn37			
Insulation material	PA			
Colour	grey			
Operating temperature	- 20 ... + 60 (- 4 ... + 140)			°C (°F)
Montage	snap fastening for 35 mm profile bars according to EN 60715			
Cable cross-section	single wire: 0.2 – 4 mm <sup>2</sup> / fine-stranded: 0.2 – 2.5 mm <sup>2</sup> / AWG 24 – AWG 12			
Insulation stripping length	8 mm			mm
Standards/approvals	IEC 83, DIN 49440-1		UL	

## Pressure compensation device

### PPC



## Mounting support

### PDR



Data	PPC	Unit
Article number	17410050000	
Thread	M12 x 1.5 - 10 mm	
Material	polyamide 6, O ring: perbunan	
Operating temperature	- 40 ... + 120 (- 40 ... + 248)	°C (°F)
Colour	RAL 7035	
System of protection	IP 66, 68 + 69K	
Sales unit	5	piece

Data	PDR	Unit
Article number	17411000000	
Fastening	self-adhesive	
Material	sheet steel, galvanised	
Operating/storage temperature	- 30 ... + 70 (- 22 ... + 158)	°C (°F)
Dimensions (HxWxD)	35 x 70 x 7	mm
Weight	approx. 25	
Load capacity after 24h waiting period	500	g